

Direct-Vent Furnaces

Model Number		Btu/hr. Input	Btu/hr. Output	Efficiency Percentages		Dimensions (Inches)			Thermostat	Shipping Weight (lbs.)
Natural	Propane			Thermal	AFUE	Width	Depth	Height		
1403822	1403821	14,000	9,800	70	65	18	7 $\frac{1}{4}$	26 $\frac{3}{4}$	Millivolt	56
2203822	2203821	22,000	16,462	75	67	32 $\frac{1}{2}$	10 $\frac{1}{4}$	28	Millivolt	98
3003822	3003821	30,000	21,000	70	66	32 $\frac{1}{2}$	10 $\frac{1}{4}$	28	Millivolt	100

* Elevation rating from sea level to 2,000'

Higher altitude models are available

1/2" Gas Connection

FEATURES

"Matchless" Pilot Igniter

All models include a "matchless" pilot igniter that assures convenient pilot lighting without matches.

No Electricity Required

Great during outages.

Thermostat Ready


Heaters can be automated with an external millivolt thermostat of your choice.

Contemporary Finish

Soft-white, powder-coat, heat-resistant finish to compliment any décor.

Interior Furnace Clearances

- 2" from an intersecting wall.
- 1 $\frac{3}{16}$ " from finished floor - 14,000 Btu/hr. models.
- 5 $\frac{1}{2}$ " from finished floor - 22,000 and 30,000 Btu/hr. models.
- 24" from top of appliance to ceiling or other obstructions - 14,000 Btu/hr. models.
- 30" from top of appliance to ceiling or other obstructions - 22,000 and 30,000 Btu/hr. models.
- 24" Maximum wall thickness.



Direct-Vent Safety

For clean, comfortable heat when and where you want it. The gas flame is completely sealed inside, away from all contact with room air. Air necessary for combustion is drawn into the chamber from outside through the vent, and combustion products are vented directly to the outside.

Only clean, gentle heat, in continuous circulation is delivered into the room. Windows and doors stay closed because no room air is used for combustion.

ACCESSORIES

High Capacity Blower

Blower is easily added to the furnace. Comes with a fully automatic fan switch. 115V power supply required. Model 2302 for 22,000 and 30,000 Btu/hr. Model 2303 for 14,000 Btu/hr. Shipping weight 6 lbs.



Vent-Cap Guard

Protects pedestrian traffic from vent-cap heat. Model 9308 - Shipping weight 3 lbs.

Vent Shield Deflector

Insulated, galvanized sheet for all direct-vent units. Model 4318 - Shipping weight 9 lbs. (Oversized)

Vent Extensions

To meet your installation needs, all models accommodate optional through-the-wall vent which may extend up to 24" maximum

Model	Length	Application	Shipping Weight
9301	15"	22038 & 30038 Series	7 lbs.
9302	24"	22038 Series	10 lbs.
9303	24"	14038 & 30038 Series	10 lbs.
9304	15"	14038 Series	7 lbs.

Face Panels

Model	Application	Shipping Weight
4309	14038 Series	16 lbs.
4333	22038 & 30038 Series	29 lbs.

Thin-Wall Collar Kit

Model 9307 - For wall thicknesses from 1" to 5". Installs with vent kit. Shipping weight 4 lbs.

Conversion Kits

Model Series	Natural to Propane	Propane to Natural
14038	8939	8942
22038	8940	8943
30038	8941	8944



IMPORTANT

- Read owner's manual before using/installing.
- Photographs are representative only.
- Check local codes and ordinances for permitted uses.
- Consult installation manual for clearances prior to installation.
- We reserve the right to amend product specifications without notice.
- Installation and servicing recommended by a qualified service person.
- Please read the warranty for any limitations of disclaimers.
- Combustion chamber carries a 10-year limited warranty. All other parts carry a one-year limited warranty.
- Venting must comply with the installation manual.
- Massachusetts Approval G3-0816-23 and G1-1215-244.

WILLIAMS

facebook.com/WilliamsProducts • linkedin.com/company/williams • twitter.com/WilliamsProduct • instagram.com/williamsproducts
youtube.com/user/WilliamsProducts

250 West Laurel Street
Colton, California 92324 USA
T | 909.825.0993
F | 909.824.8009



WARNING This product can expose you to chemicals including epichlorohydrin which is known to the State of California to cause cancer and birth defects and/or other reproductive harm. For more information go to www.p65warnings.ca.gov